

SH



呼稱 호 칭 Model	外徑 외경(mm) Outer Dia.	內徑 내경(mm) Inner Dia.	自由長 자유장(mm) Free length	定數 정수(kgf/mm) spring constant	30万 (0.3million)		50万 (0.5 million)		100万 (1 million)	
					變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load
SH 6×15	6	3	15	3.90	3.6	14	3.2	13	2.9	11
20			20	2.90	4.8		4.3		3.8	
25			25	2.30	6.0		5.4		4.8	
30			30	1.90	7.2		6.5		5.8	
35			35	1.70	8.4		7.6		6.7	
40			40	1.50	9.6		8.6		7.7	
45			45	1.30	10.8		9.7		8.6	
50			50	1.20	12.0		10.8		9.6	
55			55	1.10	13.2		11.9		10.6	
60			60	1.00	14.4		13.0		11.5	
65			65	0.90	15.6		13.8		12.48	
70			70	0.83	16.8		14.9		13.44	
SH 8×10			8	4	10		8.80		2.4	
15	15	5.86			3.6	3.2	2.9			
20	20	4.40			4.8	4.3	3.8			
25	25	3.52			6.0	5.4	4.8			
30	30	2.93			7.2	6.5	5.8			
35	35	2.51			8.4	7.6	6.7			
40	40	2.20			9.6	8.6	7.7			
45	45	1.95			10.8	9.7	8.6			
50	50	1.76			12.0	10.8	9.6			
55	55	1.60			13.2	11.9	10.6			
60	60	1.47			14.4	13.0	11.5			
65	65	1.35			15.6	14.0	12.5			
70	70	1.26			16.8	15.1	13.4			
75	75	1.17	18.0	16.2	14.4					
80	80	1.10	19.2	17.3	15.4					
90	90	0.98	21.6	19.4	17.3					