

GAS SPRINGS



Sr.	Series	Body Dia in mm	Stroke in mm Available Force in	
			min - max	daN
1	NE , MG	16 , 25	10 - 125	3 - 170
2	M	12 , 15,16,19,24 , 25 , 32	7 - 125	6 - 320
3	MS	19 , 25	7 - 122	5 - 200
4	RV	19, 25, 32, 38, 45 , 50, 63, 75, 95, 120 , 150, 195.	7 - 125	170 - 19910
5	RS	19, 25, 32, 38, 45 , 50, 63, 75, 95 , 120 , 150	7 - 122	170 - 9540
6	RF	45 , 50 , 63 , 75 , 95 , 120 , 150,195	10 - 125	740 - 2385
7	RG	45 , 50 , 63 , 75 , 95 , 120	10 - 125	740 - 6630
8	RT	32 , 38 , 45 , 50 , 63 , 75 , 95 , 120 , 150	10 - 125	360 - 9540
9	S	45 , 50 , 75 , 95	6 - 125	470 - 2945
10	SC	32 , 38 , 45 , 50 , 75 , 95 , 120 , 150 , 195	10 - 300	170 - 10600
11	H	32 , 38 , 45 , 50 , 63 , 75 , 95 , 120 , 150 , 195	10 - 300	300 - 18400
12	HT	38 , 45 , 50 ,	10 - 300	495 - 940
13	LS	75 , 95 , 120 , 150 ,	25 - 300	1590 - 9540
14	ML	25 , 32 , 38 , 50 , 63 , 75 , 95 , 120 ,	Oct-80	310 - 12720
15	MP	19 , 25 , 32 , 38 , 50 , 63	Oct-80	150 - 3000
16	MQ	32	Oct-80	660
17	KE	25 , 32 , 38 , 50 , 63 , 75 , 95 , 120 , 150 ,	6 - 65	425 - 18410

NOTE - MORE DETAIL WILL BE MADE AVAILABLE ON REQUEST.