

SB



呼稱 호 칭 Model	外徑 외경(mm) Outer Dia.	內徑 내경(mm) Inner Dia.	自由長 자유장(mm) Free length	定數 정수(kgf/mm) spring constant	30万 (0.3million)		50万 (0.5 million)		100万 (1 million)	
					變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load
SB 6×15	6	3	15	6.00	3.0	18	2.7	16	2.4	14
20			20	4.50	4.0		3.6		3.2	
25			25	3.60	5.0		4.5		4.0	
30			30	3.00	6.0		5.4		4.8	
35			35	2.60	7.0		6.3		5.6	
40			40	2.30	8.0		7.2		6.4	
45			45	2.00	9.0		8.1		7.2	
50			50	1.80	10.0		9.0		8.0	
55			55	1.60	11.0		9.9		8.8	
60			60	1.50	12.0		10.8		9.6	
65			65	1.38	13.0		11.7		10.4	
70			70	1.29	14.0		12.6		11.2	
SB 8×10			8	4	10		16.94		2.0	
15	15	11.30			3.0	2.7	2.4			
20	20	8.47			4.0	3.6	3.2			
25	25	6.78			5.0	4.5	4.0			
30	30	5.65			6.0	5.4	4.8			
35	35	4.84			7.0	6.3	5.6			
40	40	4.24			8.0	7.2	6.4			
45	45	3.77			9.0	8.1	7.2			
50	50	3.39			10.0	9.0	8.0			
55	55	3.08			11.0	9.9	8.8			
60	60	2.82			12.0	10.8	9.6			
65	65	2.61			13.0	11.7	10.4			
70	70	2.42			14.0	12.6	11.2			
75	75	2.26			15.0	13.5	12.0			
80	80	2.12			16.0	14.4	12.8			
90	90	1.88	18.0	16.2	14.4					