

SM



呼稱 호 칭 Model	外徑 외경(mm) Outer Dia.	內徑 내경(mm) Inner Dia.	自由長 자유장(mm) Free length	定數 정수(kgf/mm) spring constant	30万 (0.3million)		50万 (0.5 million)		100万 (1 million)	
					變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load
SM 6×15	6	3	15	2.08	4.8	10	4.3	9	3.8	8
20			20	1.56	6.4		5.8		5.1	
25			25	1.25	8.0		7.2		6.4	
30			30	1.04	9.6		8.6		7.7	
35			35	0.89	11.2		10.1		9.0	
40			40	0.78	12.8		11.5		10.2	
45			45	0.69	14.4		13.0		11.5	
50			50	0.63	16.0		14.4		12.8	
55			55	0.57	17.6		15.8		14.1	
60			60	0.52	19.2		17.3		15.4	
65			65	0.48	20.8		18.72		16.64	
70			70	0.45	22.4		20.16		17.92	
SM 8×10			8	4	10		4.34		3.2	
15	15	2.89			4.8	4.3	3.8			
20	20	2.17			6.4	5.8	5.1			
25	25	1.74			8.0	7.2	6.4			
30	30	1.45			9.6	8.6	7.7			
35	35	1.24			11.2	10.1	9.0			
40	40	1.09			12.8	11.5	10.2			
45	45	0.97			14.4	13.0	11.5			
50	50	0.87			16.0	14.4	12.8			
55	55	0.79			17.6	15.8	14.1			
60	60	0.72			19.2	17.3	15.4			
65	65	0.67			20.8	18.7	16.6			
70	70	0.62			22.4	20.2	17.9			
75	75	0.58			24.0	21.6	19.2			
80	80	0.54			25.6	23.0	20.5			
90	90	0.48	28.8	25.9	23.0					